

AMENDMENTS TO THE SPECIFICATION:

Please replace the paragraph beginning on page 1, line 5 with the following:

\_\_\_\_\_ This application is a continuation-in-part of U.S. patent application Ser. No. 09/954,420 filed Sep. 17, 2001 that matured into U.S. Patent No. 6,691,411 and a continuation-in-part of U.S. patent application Ser. No. 10/229,533 filed Aug. 28, 2002 that matured into U.S. Patent No. 6,675,406 which was a continuation of abandoned U.S. patent application Ser. No. 09/593,724, filed Jun. 13, 2000.

Please replace the paragraph beginning on page 7, line 10 with the following:

Referring to FIG. 6, when installing the waste water drain 29, the method begins by inserting a generally L-shaped drain pipe 16A through a drain hole 18A on the bottom wall 26 of the bathtub 20. The drain pipe 16A has both an upper end 20A and an inner end 22A. The upper end terminates in an annular flange 24A and in one embodiment is covered by a membrane 26A. Membrane 26A in one embodiment is a flat planar membrane of continuous construction that dwells in a single plane. Also, near the upper end 20A of the drain pipe 16A is a threaded portion 28A. The drain pipe 16A is inserted into the drain hole 18A, such that the annular flange 24A rests on the bottom wall 26 of the bathtub 20. A sealant material is placed on a lower surface of the annular flange 24A for securing the annular flange to the bottom wall 26 of the bathtub 20.

Please replace the paragraph beginning on page 7, line 23 with the following:

Next, a lock washer 30A is slidably mounted over the inner end 22A of the drain pipe 16A until it reaches the threaded portion 28A near the upper end 20A of the drain pipe 16A. There, lock washer 30A, which is threadably received on the threaded portion 28A, is tightened against the lower surface 32A of the bottom wall 26 of the bathtub 20.

Please replace the paragraph beginning on page 9, line 25 with the following:

\_\_\_\_\_ Fig. 8 shows a flow chart of a method for conducting a fluid leak test on a fluid system comprising a bathtub 20 which has a bottom 26 and adjacent and end wall 24, and an overflow port 30 in an end wall 24 with the bottom 26 having a waste water drain 29, and with the overflow port 30 and the waste water drain 29 being in communication with a primary drain system 34A. The steps comprise sealing a thin diaphragm 80, 26A over the overflow port 30 and the waste water drain 29 as shown in box 110. Then, charging the primary drain system 34A with fluid to conduct the leakage test as shown in box 112. The next step involves purging the primary drain system 34A of fluid, as shown in box 114. The step shown in box 116 involves opening the diaphragm 26A to thereafter permit the flow of fluid through the overflow port 30. The final step is wherein the diaphragm 26A is opened by physically cutting it open to permit fluid flow as shown in box 118.